



## CEMENTITIOUS REPAIR MORTARS

The FOSROC RENDEROC range comes in a ready to use blend of dry powders. Simply add clean water on site to produce a highly consistent cementitious repair mortar.

FOSROC RENDEROC FC – Fairing mortar screed, polymer modified (0mm – 3mm thick) applied in thin layers with a trowel to smooth and repair surface imperfections.

FOSROC RENDEROC HB – General purpose, economical, lightweight patch repair mortar for the reinstatement of large areas of concrete and for small, localised repairs. Its alkaline nature protects embedded steel reinforcement and the hardened concrete is strong, durable, resistant to chloride and carbon dioxide and has excellent thermal and water repellent properties. Applied by trowel or spraying.

FOSROC RENDEROC HB25 – Cementitious repair mortar compatible with concrete 15-30 MPa applied by wet spray or hand trowelling. High performance, lightweight with very low shrinkage.

FOSROC RENDEROC HB40 – Cementitious repair mortar for the reinstatement of large areas of reinforced concrete where low permeability and high compression strength is required. Engineered for the repair of columns and beams but also suitable for soffits and other overhead or patch repair work. Compatible with concrete 30-45 MPa, high performance, medium weight with very low shrinkage. Applied by gloved hand or trowelled.

FOSROC RENDEROC LA55 – High performance, free flowing, low alkali, micro concrete reinstatement mortar for large structural sections of concrete and smaller sections where trowelling is impractical. Its alkaline nature protects embedded steel reinforcement, it is resistant to chloride and carbon dioxide and suitable for electro-chemical repairs. Applied in sections between 50mm to 200mm thick achieving 60 Mpa in 28 days.



## FOSROC NITOBOND HAR – PRIMER

Nitobond HAR is a single component polymer emulsion systems designed as bonding agent for Renderoc concrete repair products.



Description	Code Number
Parchem Nitobond EP 1.5ltr	PARNBEP1.5
Parchem Nitobond HAR 5ltr	PARNB5
Parchem Nitobond HAR 20ltr	PARNB20

## CONCURE A99 – WATER BASED CONCRETE CURING COMPOUND

Recommended for applications to the surface of freshly laid concrete including renders, structural and mass concrete indoors and outdoors and particularly in situations where other conventional means of wet curing are difficult to maintain.



Description	Code Number
Parchem Renderoc FC 15kg	PARFC15
Parchem Renderoc HB 15kg	PARHB15
Parchem Renderoc HB25 15kg	PARHB2515
Parchem Renderoc HB40 20kg	PARHB4020
Parchem Renderoc HB70 20kg	PARHB7020
Parchem RenderocLA55 20kg	PARLA55

## RUBBING STONE

Used for heavy-duty applications such as rubbing floors and concrete, cleaning and scouring casting, and removing mould marks. Rubbing stone will help you to make your work look polished and professional.



Description	Code Number
Concrete Rubbing Block Coarse 30	CRB30C
Concrete Rubbing Block Handle Coarse 30	CRB30
Concrete Rubbing Block Medium 60	CRB60C
Concrete Rubbing Block Handle Medium 30	CRB60

